



# CLAY LUBRICANT

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)  
Issue date: 6/20/2023 Revision date: 8/28/2023 Supersedes: 7/25/2023 Version: 2.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Name : CLAY LUBRICANT

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Automotive Care Products.

#### 1.3. Supplier

3D International LLC  
20724 Centre Pointe Pkwy #1  
Santa Clarita, CA, 91350  
USA  
T (888) 999-7627

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 1-800-424-9300

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS classification

Flammable liquids Category 4 H227 Combustible liquid  
Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS labeling

Signal word (GHS) : Warning  
Hazard statements (GHS) : H227 - Combustible liquid  
Precautionary statements (GHS) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P370+P378 - In case of fire: Use media other than water to extinguish.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

#### 2.3. Other hazards which do not result in classification

No additional information available

#### 2.4. Unknown acute toxicity (GHS)

Not applicable

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS classification
Isopropanol	CAS-No.: 67-63-0	3 – 5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

# CLAY LUBRICANT

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Comments : \*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret  
Full text of hazard classes and H-statements : see section 16

---

### SECTION 4: First-aid measures

---

#### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Gently wash with plenty of soap and water. Wash contaminated clothing before reuse.  
First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water.  
First-aid measures after ingestion : Call a POISON CENTER or doctor/physician if you feel unwell.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

---

### SECTION 5: Fire-fighting measures

---

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry powder. Foam. Water fog.  
Unsuitable extinguishing media : None known.

#### 5.2. Specific hazards arising from the chemical

Fire hazard : Combustible liquid. Does not sustain combustion.  
Explosion hazard : May form flammable/explosive vapor-air mixture.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Do not allow run-off from fire fighting to enter drains or water courses.  
Protection during firefighting : Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

---

### SECTION 6: Accidental release measures

---

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid all eye and skin contact and do not breathe vapor and mist. Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

##### 6.1.1. For non-emergency personnel

Protective equipment : Refer to section 8.2.  
Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Refer to section 8.2.  
Emergency procedures : Stop leak if safe to do so.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so.  
Methods for cleaning up : Wipe up with absorbent material (for example cloth).

#### 6.4. Reference to other sections

Section 13: Disposal information. Section 7: Safe handling. Section 8: Personal protective equipment.

# CLAY LUBRICANT

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable. Keep away from Sources of ignition. - No smoking.
Precautions for safe handling	: Avoid all eye and skin contact and do not breathe vapor and mist. No open flames. No smoking.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	: Keep container tightly closed. Keep in fireproof place.
Incompatible products	: Strong acids. Strong bases. Strong oxidizers.
Incompatible materials	: Heat sources.
Heat-ignition	: Keep away from heat, sparks and flame.
Storage area	: Store in dry, cool, well-ventilated area.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

<b>CLAY LUBRICANT</b>	
No additional information available	
<b>Isopropanol (67-63-0)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	2-Propanol
ACGIH TWA (mg/m <sup>3</sup> )	490 mg/m <sup>3</sup>
ACGIH OEL TWA [ppm]	200 ppm
ACGIH STEL (mg/m <sup>3</sup> )	960 mg/m <sup>3</sup>
ACGIH OEL STEL [ppm]	400 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2022
<b>USA - ACGIH - Biological Exposure Indices</b>	
Local name	2-PROPANOL
BEI (BLV)	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B, Ns
Regulatory reference	ACGIH 2022
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Isopropyl alcohol
OSHA PEL (TWA) [1]	980 mg/m <sup>3</sup>
OSHA PEL (TWA) [2]	400 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL (TWA)	980 mg/m <sup>3</sup>
NIOSH REL TWA [ppm]	400 ppm

# CLAY LUBRICANT

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Isopropanol (67-63-0)	
NIOSH REL (STEL)	1225 mg/m <sup>3</sup>
NIOSH REL STEL [ppm]	500 ppm

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Avoid splashing. Ensure good ventilation of the work station.  
Environmental exposure controls : Prevent leakage or spillage.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Avoid all unnecessary exposure.

<b>Hand protection:</b>
Wear suitable gloves.
<b>Eye protection:</b>
In case of splashing or aerosol production: protective goggles.
<b>Respiratory protection:</b>
No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation.

#### Other information:

Do not eat, drink or smoke when using this product.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid
Color	: Green
Odor	: Fruity
Odor threshold	: No data available
pH	: 6 – 7
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 91 – 93 °C
Flash point	: ≈ 60.8 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 1
Solubility	: Soluble in water
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: ≈ 1 mm <sup>2</sup> /s @20° C
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

# CLAY LUBRICANT

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reactions known.

#### 10.2. Chemical stability

Combustible liquid. Does not sustain combustion.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Heat. Open flame. Overheating. Direct sunlight. Sparks.

#### 10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

#### 10.6. Hazardous decomposition products

None under normal use. May release flammable gases.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

Isopropanol (67-63-0)	
LD50 Oral rat	5840 mg/kg
LD50 Dermal rabbit	16.4 ml/kg
LC50 Inhalation rat [ppm]	> 10000 ppm/4h
ATE (oral)	5840 mg/kg body weight
ATE (dermal)	13120 mg/kg body weight

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

Isopropanol (67-63-0)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified  
STOT-single exposure : Not classified

Isopropanol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified  
Aspiration hazard : Not classified  
Viscosity, kinematic :  $\approx 1 \text{ mm}^2/\text{s}$  @20° C  
Likely routes of exposure : Skin and eye contact. Inhalation.  
Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

# CLAY LUBRICANT

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

### SECTION 12: Ecological information

#### 12.1. Toxicity

Isopropanol (67-63-0)	
LC50 fish 1	10000 mg/l

#### 12.2. Persistence and degradability

Isopropanol (67-63-0)	
Persistence and degradability	Readily biodegradable.

#### 12.3. Bioaccumulative potential

Isopropanol (67-63-0)	
Log Pow	0.05
Bioaccumulative potential	Not expected to bioaccumulate.

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.  
Additional information : Handle empty containers with care because residual vapors are flammable.

### SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

#### 14.1. UN number

Not regulated for transport

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable  
Proper Shipping Name (TDG) : Not applicable  
Proper Shipping Name (IMDG) : Not applicable  
Proper Shipping Name (IATA) : Not applicable

#### 14.3. Transport hazard class(es)

##### DOT

Transport hazard class(es) (DOT) : Not applicable

##### TDG

Transport hazard class(es) (TDG) : Not applicable

##### IMDG

Transport hazard class(es) (IMDG) : Not applicable

# CLAY LUBRICANT

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

### IATA

Transport hazard class(es) (IATA) : Not applicable

### 14.4. Packing group

Packing group (DOT) : Not applicable

Packing group (TDG) : Not applicable

Packing group (IMDG) : Not applicable

Packing group (IATA) : Not applicable

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

#### DOT

No data available

#### TDG

No data available

#### IMDG

No data available

#### IATA

No data available

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Isopropanol	67-63-0	Present	Active	

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Isopropanol	CAS-No. 67-63-0	3.71%
-------------	-----------------	-------

#### Isopropanol (67-63-0)

SARA Section 311/312 Hazard Classes	Fire hazard
-------------------------------------	-------------

### 15.2. International regulations

#### CANADA

#### Isopropanol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

No additional information available

# CLAY LUBRICANT

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

### National regulations

#### Isopropanol (67-63-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### 15.3. US State regulations

No additional information available

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Revision date

: 08/28/2023

Data sources

: ACGIH (American Conference of Government Industrial Hygienists). European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. OSHA 29CFR 1910.1200 Hazard Communication Standard. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

Other information

: None.

### Full text of H-phrases

H225	Highly flammable liquid and vapor
H227	Combustible liquid
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

### Abbreviations and acronyms

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	OSHA: Occupational Safety & Health Administration
	TSCA: Toxic Substances Control Act
	STEL: Short Term Exposure Limits
	TWA: Time Weighted Average

NFPA health hazard


: 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard

: 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.





# CLAY LUBRICANT

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Indication of changes:			
Section	Changed item	Change	Comments
	Additional information	Added	Added jurisdiction - Canada.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.